

Special Solutions

Replacement tubes for **POLYPHOS**



Nominal Power (kW)	Rated Focal Spot	Anode Speed	Anode Material	Anode Angle (°)	Anode Heat Storage Capacity	Maximal Voltage (kV)	Comment
30 / 50	0,8 / 1,2	200 Hz	RTM	16	110 kWhU = 81 kJ	125	(1)
30 / 50	0,8 / 1,2	200 Hz	RTMC	16	270 kWhU = 200 kJ	125	(2)

(1) *Qualified for medium load !*

(2) *Qualified for high load !*

Replacement tubes for **TuR** assemblies

Data of the Replacement Tubes

Tube to replace	Rated Focal Spot	Anode Heat Storage Capacity	Anode Material	Anode Angel (°)
DR 124 / 4/ 30	0,4 / 1,2	150 kWhU = 111 kJ	T	17,5
DR 124 / 12/ 30	0,6 / 1,2	150 kWhU = 111 kJ	T	17,5
DR 124 / 12/ 50	0,6 / 2,0	150 kWhU = 111 kJ	T	17,5
DR 124 / 30/ 50	1,2 / 2,0	150 kWhU = 111 kJ	T	17,5
DR 154 / 4/ 30	0,4 / 1,2	150 kWhU = 111 kJ	T	17,5
DR 154 / 12/ 30	0,6 / 1,2	150 kWhU = 111 kJ	T	17,5
DR 154 / 12/ 50	0,6 / 2,0	150 kWhU = 111 kJ	T	17,5
DR 154 / 30/ 50	1,2 / 2,0	150 kWhU = 111 kJ	T	17,5
DRX 124 / 12/ 30	0,3 / 0,6	300 kWhU = 222 kJ	RTM	12
DRX 124 / 12/ 60	0,3 / 1,2	300 kWhU = 222 kJ	RTM	12
DRX 124 / 30/ 60	0,6 / 1,2	300 kWhU = 222 kJ	RTM	12
DRX 124 / 30/ 50	0,8 / 1,2	300 kWhU = 222 kJ	RTM	16
DRX 154 / 30/ 50	0,6 / 1,2	300 kWhU = 222 kJ	RTM	12

*All models are equipped with the special TuR tube mount with bayonet base.
More models on request!*